



Product Size	400ml
Gross Weight	383g
Net Weight	288g
UN Number	1950
Custom Code	3403.19.00
Country of Manufacture	RSA
Barcode	6001690300078
Article Number	030007

CHARACTERISTICS	
Colour	Clear
Texture	Liquid
Odour	Aromatic
Temp Range	<=35 °C

PACKAGING	
Type	Card Box
Dimensions	H:21 W:21 L:27cm
Box Weight	4.63 kg
Packaging Group	Class II
Valve Type	360°
Cap	Translucent Blue
Pack Type	Aerosol
Units in Carton	12

Product Description

✔ QUICK ACTING ✔ RELEASES SEIZED FITTINGS ✔ PREVENTS CORROSION

Q10 PENETRATING OIL is a quick-acting, penetrating rust solvent and release agent for rusted or seized nuts, bolts, pipe fittings etc.

Available in 150 ml / 400 ml / 500ml / 1 lt / 5 lt / 20 lt / 1000 lt

Ideal Usage



Application of Product

Directions:

Shake well before use. Q10 PENETRATING OIL works best when the nozzle is pressed down firmly. Spray on to the seized parts. Allow a short time to penetrate, then slowly loosen parts. Keep applying as parts are being loosened.

Test Results/Approvals/Certificates

N/A

Safety Data Sheet Summary

Classification of the substance or mixture

Classification under CHIP: F+: R12

Classification under CLP: Flam. Aerosol 1: H222; -: EUH066

Most important adverse effects: Extremely flammable.

Label elements

Hazard statements: H222: Extremely flammable aerosol.
EUH066: Repeated exposure may cause skin dryness or cracking.

Signal words: Danger

Hazard pictograms: GHS02: Flame



Precautionary statements: P202: Do not handle until all safety precautions have been read and understood.
P281: Use personal protective equipment as required.
P302+350: IF ON SKIN: Gently wash with plenty of soap and water.
P211: Do not spray on an open flame or other ignition source.
P251: Pressurized container: Do not pierce or burn, even after use.
P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

Safety Data Sheet Summary**Label elements under CHIP:**

Hazard symbols: Extremely flammable.



Risk phrases: R12: Extremely flammable.

Safety phrases: S2: Keep out of the reach of children.
S29: Do not empty into drains.
S51: Use only in well-ventilated areas.

Precautionary phrases: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.