



Product Size	150ml
Gross Weight	154g
Net Weight	107g
UN Number	1950
Custom Code	3403.19.00
Country of Manufacture	RSA
Barcode	6001690300054
Article Number	030005

CHARACTERISTICS	
Colour	Grey
Texture	Liquid
Odour	Aromatic
Temp Range	<=35 °C

PACKAGING	
Type	Card Box
Dimensions	H:14.5 W:22 L:32.5cm
Box Weight	4 kg
Packaging Group	Class II
Valve Type	360°
Cap	Translucent Blue
Pack Type	Aerosol
Units in Carton	24

Product Description

✓ QUICK ACTING ✓ RELEASES SEIZED FITTINGS ✓ PREVENTS CORROSION

Q5 is a graphite-based quick-acting penetrating and release agent for rusted nuts, bolts, pipes and fittings. Q5 GRAPHITE-BASED PENETRATING OIL works wonders on lubricating and loosening locks, leaving a layer of graphite behind which acts as an anti-static dry lubricant.

Ideal Usage



Application of Product**Directions:**

Shake well before use. Q5 GRAPHITE-BASED PENETRATING OIL works best when the nozzle is pressed down firmly. Spray onto the surface to be treated and do not wipe off.

Test Results/Approvals/Certificates

N/A

Safety Data Sheet Summary**Classification of the substance or mixture**

Classification under CHIP: F+: R12

Classification under CLP: Flam. Aerosol 1: H222; -: EUH066

Most important adverse effects: Extremely flammable.

Label elements**Label elements under CLP:**

Hazard statements: H222: Extremely flammable aerosol.

EUH066: Repeated exposure may cause skin dryness or cracking.

Signal words: Danger

Hazard pictograms: GHS02: Flame



Precautionary statements: P202: Do not handle until all safety precautions have been read and understood.
P281: Use personal protective equipment as required.
P302+350: IF ON SKIN: Gently wash with plenty of soap and water.
P211: Do not spray on an open flame or other ignition source.
P251: Pressurized container: Do not pierce or burn, even after use.
P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

Safety Data Sheet Summary**Label elements under CHIP:**

Hazard symbols: H222: Extremely flammable aerosol.



Risk phrases: R12: Extremely flammable.

Safety phrases: S2: Keep out of the reach of children.
S29: Do not empty into drains.
S51: Use only in well-ventilated areas.

Precautionary phrases: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
Do not spray on a naked flame or any incandescent material.
Keep away from sources of ignition - No smoking.
Keep out of the reach of children.